


Lashing Gear Type

	10.0	15.0	20.2	20.0	20.4	30.0	30.1	40.0
Grab Size	0,28 m ³	0,42 m ³	0,56 m ³	0,56 m ³	0,56 m ³	0,85 m ³	0,85 m ³	1,12 m ³
Finished Shaft-ø m	< 4,5	< 6,0	< 7,0	< 8,0	< 9,0	< 9,5	< 11,0	< 11,5
Turntable-ø mm	1135	1200	1320	1600	1850	2000	2250	2500
Slew Bearing-ø mm	1020	1084	1180	1350	1680	1680	1850	2200
Square Base mm	1030	1090	1180	1380	1680	1680	2000	2240
Size A (square) mm	900	960	1080	1240	1540	1540	1800	2000
Size B mm	900	1000	1050	1050	1100	1100	1100	1250
L.G. Mass	3500 kg	7000 kg	8250 kg	9500 kg	10500kg	12000kg	13000kg	14000kg
Live Load	2160 kg	4000 kg	4200 kg	4200 kg	4200 kg	6000 kg	6000 kg	8000 kg
Shock Factor	3	3	3	3	3	3	3	3

WINDER CONTROLS

Winder Controls (Pty.) Ltd.
 P.O.Box 383, Germiston 1400, South Africa
 Listed by SABS  0157 Part 1
 Tel. (011) 873-4650
 Fax. (011) 873-4728



<< Back to previous page

Standard Range of Lashing Gears

Scale	PS 1:15	Date	Copyright Reserved
Drawn	<i>R. Laidy</i>	1992	Replacement for
Checked	<i>KSH</i>	1992	
Approved	<i>[Signature]</i>	1992	Superseded by
LG-1a			Revision